ONEHEALTH Medical

FITUR

- Hand wheel translation and quick opening structure
- High quality stainless steel material
- With drying function
- Microcomputer automatic control, arbitrary setting sterilization parameters
- Safety interlocking device
- Digital display and Touch buttons
- Standard test interface
- Self-expanding seal
- With automatic protection function:over temperature protection; over pressure self discharge protection; low water level protection; anti dry burning.
- With stainless steel bucket or basket
- Buzzer reminder after sterilization, automatic stop.
- Automatic discharge of cold air, automatic steam exhaust after sterilization, Internal steam cycle.

50L
CAPACITY



Multifunction Automatic Internal Cycle with Drying

SPESIFICATION

Volume	: 50L
Power	: 3.5 kw
Voltage	: AC 220V 50Hz
Design pressure	: 0.25MPa
Design temperature	: 139°C
Rated working pressure	: 0.22MPa
Rated working temperature	: 134°C
Sterilization temperature setting range	: 116°C-134°C
Sterilization time setting range	: 4~120 min
Drying time setting range	: 0~240 min
Chamber volume	: Ø 350×525
Bucket dimension	: Ø 330×460
Basket dimension	: Ø 320×240×2
Outer dimension	: 630×500×1180
Packing size (LxWxH)	: 800×600×1230
Gross/Net weight	: 121/101kg

VERTICALSTEAM STERILIZER (50L)

KEMENTERIAN KESEHATAN REPUBLIK INDONESIA

KEMENKES RI AKL 20903420944