



YX102 YX110

Automatic shutdown
Pulse column display
Bluetooth
LED backlit display

- Measurement range of pulse rate: 25bpm~250bpm
- Accuracy of SpO2: 70%~100%: ±2%
- Accuracy of pulse rate:
  ±1% / ±1bpm (The result depends on the larger value)
- Power consumption: ≤40mA
- Operation environment: Temperature(℃): 5~40
  Relative humidity: ≤80%
- Boot method: Open angle to boot
- Power supply: 2×1.5V AAA alkaline batteries
- Display mode: LED
- Dimension: 60×38×35mm
- Weight: 38g (without batteries)
- Automatic shutdown time: 8s

QTN: 40PCS/CTN
G.W./N.W.: 4.1/1.5kg
Size: 45×26×15cm

YX306 YX310

Automatic shutdown
OLED display
Pulse wave display
Bluetooth
Gravity sense function
Pulse column display
PI display

- Measurement range of pulse rate: 25bpm~250bpm
- Accuracy of SpO2: 70%~100%: ±2%
- Accuracy of pulse rate:
  ±1% / ±1bpm(The result depends on the larger value)
- Power consumption: ≤40mA
- Operation environment: Temperature(℃): 5~40
  Relative humidity: ≤80%
- Boot method: Push button to boot
- Power supply: 2×1.5V AAA alkaline batteries
- Dimension: 60×38×35mm
- Weight: 38g (without batteries)
- Automatic shutdown time: 8s

QTN: 40PCS/CTN
G.W./N.W.: 4.1/1.5kg
Size: 45×26×15cm